SAFETY DATA SHEET
(in accordance with Regulation (EU) 2020/878)

0056-Netoline

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: Netoline
Product Code: 0056
UFI: C250-S00D-8004-URJC

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Descaling detergent

Uses advised against:
Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **FLUIDRA COMMERCIAL, S.A.U.**
Address: Av. Alcalde Barnils, 69
City: 08174 Sant Cugat del Vallès (Barcelona) Spain
Province: Barcelona
Telephone: Tel:34 93 724 39 00 Fax:34 93 724 29 93
Fax: +34 93 713 41 11
E-mail: fds@inquide.com
Web: www.astralpool.com

1.4 Emergency telephone number: +34 93 724 39 00 (Only available during office hours; Monday-Friday; 08:00-18:00)
Anti poisoning centre:
ITALY (Rome): 06/305 43 43
ITALY (Milan): 02/66 10 10 29
SPAIN: +34 91 562 04 20
FRANCE (Paris): 01 40 05 48 48 FRANCE (Tolousse): 05 61 77 74 47 FRANCE (Marseille): 04 91 75 25 25
PORTUGAL: 808 250 143
BELGIQUE (Brussel): (+32) 070 245 245
Sweden: 112 - Begär Giftinformation (ask for Poisons Information)
Denmark (Giftlinjen): +45 8212 1212
Finland: 0800 147 111
Norway: +47 22 59 13 00
Cyprus: 1401
Greece: (0030) 2107793777
Netherlands (NVIC): +31 (0)88 755 8000
Romania: +4021 318 360 6 Biroul RSI Si Informare Toxicologica
Apelabil de luni pâna vineri, între orele 8.00-15.00
CAV accreditati: Roma +39 06 68 59 3726; Foggia +39 800 18 34 59; Napoli +39 081 54 53 333; Roma +39 06 49 97 80 00; Roma +39 06 30 54 343; Firenze +39 055 79 47 819; Pavia +39 0382 24 444; Milano +39 02 66 10 10 29; Bergamo +39 800 88 33 00; Verona +39 800 01 18 58.

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.
In accordance with Regulation (EU) No 1272/2008:
STOT SE 3 : May cause respiratory irritation.
Skin Corr. 1 : Causes severe skin burns and eye damage.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:
Pictograms:

-Continued on next page.-




Signal Word:
Danger
Hazard statements:
H335 May cause respiratory irritation.
H314 Causes severe skin burns and eye damage.

Precautionary statements:
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P280 Wear protective gloves/protective clothing/eye protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER or a doctor.
P405 Store locked up.

Keep out of the reach of children.
Keep only in original container.
Contains:
hydrochloric acid
Amines, tallow alkyl, ethoxylated

2.3 Other hazards.

The mixture does not contain substances classified as PBT.
The mixture does not contain substances classified as vPvB.
The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.
Not Applicable.

3.2 Mixtures.
Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	Specifics concentration limits and Acute toxicity estimate
Index No: 017-002-01-X CAS No: 7647-01-0 EC No: 231-595-7 Registration No: 01-2119484862-27-XXXX	hydrochloric acid	10 - 25 %	STOT SE 3, H335 - Skin Corr. 1B, H314	Skin Corr. 1B, H314: C ≥ 25 % Skin Irrit. 2, H315: 10 % ≤ C < 25 % Eye Irrit. 2, H319: 10 % ≤ C < 25 % STOT SE 3, H335: C ≥ 10 %

-Continued on next page.-

CAS No: 61791-26-2 EC No: 500-153-8	Amines, tallow alkyl, ethoxylated	1 - 3 %	Acute Tox. 4, H302 - Aquatic Acute 1, H400 - Skin Corr. 1B, H314	-
Index No: 603-117-00-0 CAS No: 67-63-0 EC No: 200-661-7 Registration No: 01-2119457558-25-XXXX	propan-2-ol	0 - 10 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	-

(*) *The complete text of the H phrases is given in section 16 of this Safety Data Sheet.*

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.
In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.
Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.
Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.
Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.
If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.
Corrosive Product, contact with eyes or skin can cause burns; ingestion or inhalation can cause internal damage, if this occurs immediate medical assistance is required.

4.3 Indication of any immediate medical attention and special treatment needed.
In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Cover the affected area with a dry sterile bandage. Protect the affected area from pressure or friction.

SECTION 5: FIREFIGHTING MEASURES.

The product is NOT classified as flammable, in case of fire the following measures should be taken:

5.1 Extinguishing media.
Suitable extinguishing media:
Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:
Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.
Special risks.
Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.
Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

-Continued on next page.-

Fire protection equipment.
According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.
For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.
Product not classified as hazardous for the environment, avoid spillage as much as possible.

6.3 Methods and material for containment and cleaning up.
Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.
Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

6.4 Reference to other sections.
For exposure control and individual protection measures, see section 8.
For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.
For personal protection, see section 8.
In the application area, smoking, eating, and drinking must be prohibited.
Follow legislation on occupational health and safety.
Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.
Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 º C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).
None in particular.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m³
propan-2-ol	67-63-0	United Kingdom [1]	**Eight hours**	400	999
			Short term	500	1250
		Éire [2]	**Eight hours**	200	
			Short term	400	
		Italia [3]	**Eight hours**	200	
			Short term	400	
		United States [4] (Cal/OSHA)	**Eight hours**	400	
			Short term	500	
		United States [5] (NIOSH)	**Eight hours**	400	
			Short term	500	

-Continued on next page.-

		United States [6] (OSHA)	**Eight hours**	400	980
			Short term		

[1] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adobted by Health and Safety Executive.
[2] According Code of Practice for the Safety, Health and Welfare at Work (Chemicals Agents) Regulations adopted by Health and Safety Authority (HSA).
[3] Secondo il Decreto Legislativo del Governo n.277, 15/08/1991, il Decreto Legislativo n.66 ed il Decreto Ministeriale 26/02/2004.
[4] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).
[5] National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health, Compendium of Policy Documents and Statements, January, 1992, DHHS (NIOSH) Publication No. 92-100.
[6] Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs), California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).
The product does NOT contain substances with Biological Limit Values.
Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
propan-2-ol CAS No: 67-63-0 EC No: 200-661-7	DNEL (Workers)	Inhalation, Chronic, Systemic effects	500 (mg/m³)
	DNEL (Consumers)	Inhalation, Chronic, Systemic effects	89 (mg/m³)
	DNEL (Workers)	Dermal, Chronic, Systemic effects	888 (mg/kg bw/day)
	DNEL (Consumers)	Dermal, Chronic, Systemic effects	319 (mg/kg bw/day)
	DNEL (Consumers)	Oral, Chronic, Systemic effects	26 (mg/kg bw/day)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
Concentration levels PNEC:

Name	Details	Value
propan-2-ol CAS No: 67-63-0 EC No: 200-661-7	aqua (freshwater)	140,9 (mg/L)
	aqua (marine water)	140,9 (mg/L)
	aqua (intermittent releases)	140,9 (mg/L)
	sediment (freshwater)	552 (mg/kg sediment dw)
	sediment (marine water)	552 (mg/kg sediment dw)
	Soil	28 (mg/kg soil dw)
	STP	2251 (mg/L)
	oral (Hazard for predators)	160 (mg/kg food)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

8.2 Exposure controls.

Measures of a technical nature:
Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	**100 %**
Uses:	**Descaling detergent**
Breathing protection:	
PPE:	Filter mask for protection against gases and particles.
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.
CEN standards:	EN 136, EN 140, EN 405
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.



-Continued on next page.-

Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.
Filter Type needed:	A2

Hand protection:

PPE:	Non-disposable protective gloves against chemicals.
Characteristics:	«CE» marking, category III. Check the list of chemicals for which the glove has been tested.
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420
Maintenance:	A schedule for the periodical replacement of gloves should be established in order to guarantee their replacement before pollutants permeate them. The use of contaminated gloves could be more dangerous than not using gloves, since the pollutant can gradually accumulate in the glove's material.
Observations:	They are to be replaced whenever tears, cracks or deformations are observed or when exterior dirt could reduce their strength.



Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480	Material thickness (mm):	0,35

Eye protection:

PPE:	Protective goggles with built-in frame.
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.
CEN standards:	EN 165, EN 166, EN 167, EN 168
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.



Skin protection:

PPE:	Chemical protective clothing
Characteristics:	«CE» marking, category III. Clothing should fit properly. The level of protection must be set according to a test parameter called BT (Breakthrough Time), which indicates how long it takes for the chemical to pass through the material.
CEN standards:	EN 464,EN 340, EN 943-1, EN 943-2, EN ISO 6529, EN ISO 6530, EN 13034
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.
Observations:	The protective clothing's design should facilitate correct positioning, staying in place without moving for the period of use expected, bearing in mind environmental factors as well as any movement or position the user might adopt while carrying out the activity.



PPE:	Anti-static safety footwear against chemicals.
Characteristics:	«CE» marking, category III. Check the list of chemicals against which the footwear is resistant.
CEN standards:	EN ISO 13287, EN 13832-1, EN 13832-2, EN 13832-3, EN ISO 20344, EN ISO 20345
Maintenance:	For correct maintenance of this kind of safety footwear, it is necessary to observe the instructions specified by the manufacturer. The footwear should be replaced as soon as any sign of damage is observed.
Observations:	The footwear should be cleaned regularly and dried when damp, although it should not be placed too close to a source of heat in order to avoid any sharp changes in temperature.



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.
Physical state: Liquid
Colour: Pale pink
Odour: Characteristic (spicy)
Odour threshold: Not applicable/Not available due to the nature/properties of the product
Melting point: Not applicable/Not available due to the nature/properties of the product
Freezing point: Not applicable/Not available due to the nature/properties of the product
Boiling point or initial boiling point and boiling range: >100 ºC
Flammability: Not applicable/Not available due to the nature/properties of the product
Lower explosion limit: Not applicable/Not available due to the nature/properties of the product
Upper explosion limit: Not applicable/Not available due to the nature/properties of the product
Flash point: 187 ºC (Estimation based on the indication of the Regulation (CE) Nº1272/2008.)
Auto-ignition temperature: Not applicable/Not available due to the nature/properties of the product
Decomposition temperature: Not applicable/Not available due to the nature/properties of the product

-Continued on next page.-

pH: 0,5 (5%)
Kinematic viscosity: Not applicable/Not available due to the nature/properties of the product
Solubility: Not applicable/Not available due to the nature/properties of the product
Hydrosolubility: 100 %
Liposolubility: Etanol, éter, benceno, acetona
Partition coefficient n-octanol/water (log value): Not applicable/Not available due to the nature/properties of the product
Vapour pressure: 23,676 (Estimation based on the indication of the Regulation (CE) Nº1272/2008.)
Absolute density: Not applicable/Not available due to the nature/properties of the product
Relative density: 1.05 - 1.09
Relative vapour density: Not applicable/Not available due to the nature/properties of the product
Particle characteristics: Not applicable/Not available due to the nature/properties of the product

9.2 Other information
Viscosity: Not applicable/Not available due to the nature/properties of the product
Explosive properties: Not applicable/Not available due to the nature/properties of the product
Oxidizing properties: No aplicable
Dropping point: Not applicable/Not available due to the nature/properties of the product
Blink: Not applicable/Not available due to the nature/properties of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.
The product does not present hazards by their reactivity.

10.2 Chemical stability.
Unstable in contact with:
- Bases.

10.3 Possibility of hazardous reactions.
Neutralization can occur on contact with bases.

10.4 Conditions to avoid.
- Avoid contact with bases.

10.5 Incompatible materials.
Avoid the following materials:
- Bases.

10.6 Hazardous decomposition products.
Depending on conditions of use, can be generated the following products:
- Corrosive vapors or gases.

SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT MIXTURE. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.
11.1 Information on hazard classes as defined in Regulation (EC) Nº 1272/2008.
Splatters in the eyes can cause irritation and reversible damage.

Toxicological information about the substances present in the composition.

Name	Acute toxicity			
	Type	Test	Kind	Value
hydrochloric acid CAS No: 7647-01-0 EC No: 231-595-7	Oral	LD50	Rat	700 mg/kg
	Dermal	LD50	Rabbit	> 5010 mg/kg
	Inhalation	LC50	Rat	4.6 mg/l
Amines, tallow alkyl, ethoxylated	Oral	LC50	Rat	2000 mg/kg
	Dermal			

-Continued on next page.-

CAS No: 61791-26-2 EC No: 500-153-8	Inhalation		
propan-2-ol	Oral	LD50 Rat 5840 mg/kg bw [1] LD50 Rat 5840 mg/kg bw [2] [1] FURTHER EXPERIENCE WITH THE RANGE FINDING TEST IN THE INDUSTRIAL TOXICOLOGY LABORATORY, J Ind Hyg Toxicol 30(1):63-68 [2] FURTHER EXPERIENCE WITH THE RANGE FINDING TEST IN THE INDUSTRIAL TOXICOLOGY LABORATORY, J Ind Hyg Toxicol 30(1):63-68
	Dermal	LD50 Rabbit 13900 mg/kg [1] [1] OCDE 402
CAS No: 67-63-0 EC No: 200-661-7	Inhalation	LC50 Rat > 25000 mg/kg [1] [1] OCDE 403

a) acute toxicity;
Not conclusive data for classification.

Acute Toxicity Estimate (ATE):
Mixtures:
ATE (Oral) = 25.000 mg/kg

b) skin corrosion/irritation;
Product classified:
Skin Corrosive, Category 1: Causes severe skin burns and eye damage.

c) serious eye damage/irritation;
Based on available data, the classification criteria are not met.

d) respiratory or skin sensitisation;
Not conclusive data for classification.

e) germ cell mutagenicity;
Not conclusive data for classification.

f) carcinogenicity;
Not conclusive data for classification.

g) reproductive toxicity;
Not conclusive data for classification.

h) STOT-single exposure;
Product classified:
Specific target organ toxicity following a single exposure, Category 3: May cause respiratory irritation.

i) STOT-repeated exposure;
Not conclusive data for classification.

j) aspiration hazard;
Not conclusive data for classification.

11.2 Information on other hazards.
Endocrine disrupting properties
This product does not contain components with endocrine-disrupting properties with effects on human health.
Other information
There is no information available on other adverse health effects.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

-Continued on next page.-

Name	Ecotoxicity			
	Type	Test	Kind	Value
hydrochloric acid CAS No: 7647-01-0 EC No: 231-595-7	Fish	LC50	Fish	282 mg/l (96 h)
	Aquatic invertebrates	EC50	Daphnia	56 mg/l (72 h)
	Aquatic plants			
Amines, tallow alkyl, ethoxylated CAS No: 61791-26-2 EC No: 500-153-8	Fish	LC50	Fish	0.99 mg/l (96 h)
	Aquatic invertebrates			
	Aquatic plants			
propan-2-ol CAS No: 67-63-0 EC No: 200-661-7	Fish	LC50 LC50	Fish Pimephales promelas	9640 mg/l (96 h) [1] 10000 mg/l (96 h) [2]
		[1] Brooke, L.T., D.J. Call, D.L. Geiger, and C.E. Northcott 1984. Acute Toxicities of Organic Chemicals to Fathead Minnows (Pimephales promelas), Vol. 1. Center for Lake Superior Environmental Stud., Univ.of Wisconsin-Superior, Superior, WI :414 [2] The 96 hour LC50 method is described by the US Environmental Protection Agency Committee on Methods for Toxicity Tests with Aquatic Organisms 1975.		
	Aquatic invertebrates	EC50 LC50	Daphnia magna Daphnia magna	9714 mg/L (24 h) [1] >10000 mg/l (24 h) [2]
		[1] Not GLP, no guideline followed, although it is similar to the most recent OECD 202 with some deviations, which did not affect results. It contains all the information necessary for the evaluation. [2] Not GLP, no guideline followed, although it is similar to the most recent OECD 202 with some deviations, which did not affect results. It contains all the information necessary for the evaluation.		
	Aquatic plants			

12.2 Persistence and degradability.
No information is available regarding the biodegradability of the substances present.
No information is available on the degradability of the substances present.
No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.
Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
propan-2-ol CAS No: 67-63-0 EC No: 200-661-7	0,05	-	-	Very low

12.4 Mobility in soil.
No information is available about the mobility in soil.
The product must not be allowed to go into sewers or waterways.
Prevent penetration into the ground.

-Continued on next page.-

12.5 Results of PBT and vPvB assessment.
No information is available about the results of PBT and vPvB assessment of the product.

12.6 Endocrine disrupting properties.
This product doesn't contain components with environmental endocrine disrupting properties.

12.7 Other adverse effects.
No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.
Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.
Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.
Land: Transport by road: ADR, Transport by rail: RID.
Transport documentation: Consignment note and written instructions
Sea: Transport by ship: IMDG.
Transport documentation: Bill of lading
Air: Transport by plane: ICAO/IATA.
Transport document: Airway bill.

14.1 UN number or ID number.
UN No: UN1760

14.2 UN proper shipping name.
Description:
ADR/RID: UN 1760, CORROSIVE LIQUID, N.O.S. (CONTAINS HYDROCHLORIC ACID), 8, PG II, (E)
IMDG: UN 1760, CORROSIVE LIQUID, N.O.S. (CONTAINS HYDROCHLORIC ACID), 8, PG II
ICAO/IATA: UN 1760, CORROSIVE LIQUID, N.O.S. (CONTAINS HYDROCHLORIC ACID), 8, PG II

14.3 Transport hazard class(es).
Class(es): 8

14.4 Packing group.
Packing group: II

14.5 Environmental hazards.
Marine pollutant: No
Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-A,S-B

14.6 Special precautions for user.
Labels: 8



Hazard number: 80
ADR LQ: 1 L
IMDG LQ: 1 L
ICAO LQ: 0,5 L

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.

-Continued on next page.-

Proceed in accordance with point 6.

14.7 Maritime transport in bulk according to IMO instruments.
The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.
The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC)
VOC content (p/p): 0,019 %
VOC content: 0,204 g/l

Preservation agents: SODIUM SULFITE
Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): N/A
The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.
The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Kind of pollutant to water (Germany): nwg: Non-hazardous to water. (Autoclassified according to the AwSV Regulations)

Information on Annex I of Comission Delegated Regulation (EU) 2020/1737 of 14 July 2020 and Annex I of Regulation (EC) No. 273/2004 of the European Parliament and of the Council of 11 February 11 2004 on drug precursors:

CAS No	Name	Category
7647-01-0	hydrochloric acid ... %	3

Annex I: List of scheduled substances.

15.2 Chemical safety assessment.
No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H225 Highly flammable liquid and vapour.
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H400 Very toxic to aquatic life.

Classification codes:

Acute Tox. 4 : Acute toxicity (Oral), Category 4
Aquatic Acute 1 : Acute toxicity to the aquatic environment, Category 1
Eye Irrit. 2 : Eye irritation, Category 2
Flam. Liq. 2 : Flammable liquid, Category 2
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3
Skin Corr. 1 : Skin Corrosive, Category 1
Skin Corr. 1B : Skin Corrosive, Category 1B

-Continued on next page.-

Changes regarding to the previous version:

- Changes in the composition of the product (SECTION 3.2).
- Changes in the composition of the product (SECTION 3.2).
- Changes in the composition of the product (SECTION 3.2).
- Addition of ecotoxicity values (SECTION 11.1).
- Addition of ecological information values (SECTION 12.1).
- National legislative changes (SECTION 15.1).

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR/RID: European Agreement concerning the International Carriage of Dangerous Goods by Road.
AwSV: Facility Regulations for handling substances that are hazardous for the water.
BCF: Bioconcentration factor.
CEN: European Committee for Standardization.
DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
EC50: Half maximal effective concentration.
PPE: Personal protection equipment.
IATA: International Air Transport Association.
ICAO: International Civil Aviation Organization.
IMDG: International Maritime Code for Dangerous Goods.
LC50: Lethal concentration, 50%.
LD50: Lethal dose, 50%.
NOEC: No observed effect concentration.
PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.
RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.
WGK: Water hazard classes.

Key literature references and sources for data:
http://eur-lex.europa.eu/homepage.html
http://echa.europa.eu/
Regulation (EU) 2020/878.
Regulation (EC) No 1907/2006.
Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.

-End of safety data sheet.-